

RJ45 Connector

C



Electrical Features:

- Dielectric Strength:1000V RMS for 1min
- Current Rating:1.5Amp Max.
- Insulation Resistance:10MΩ Min.
- Contact Resistance:2MΩ per contact

S



Mechanical Features:

- Operating temperature: -40°C to +70 °C .
- Relative Humidity: <95% (at 25°C).
- Durability: 750 mating cycles min.

ST



Material:

- Housing: Polycarbonate (PC);
Flammability Class: UL 94V-0 or UL 94V-2 2.
- Contacts: Phosphor bronze,
Nickel plating followed with gold plating: 1u to 50u micro-inch.
- Shielding Housing Brass with nickel plating or steel with nickel plating.

Operating Life:

- Jack contact: Minimum 750 insertions
- IDC contacts: Minimum 250 Re-terminations

CP



Order Information:

Type	CAT.	*Type explanation
C	5 UTP	C Common type,mainly for UTP cable
S	5E UTP	S Common type,Mainly for FTP cable
ST	6 UTP	ST FTP cable with fixing ring
CP	6A UTP	CP common type with wire protection
SB	5 FTP	SB FTP cable with boot cover
	5E FTP	
	6 FTP	
	6A FTP	

Packing : 50pcs per Box
Warranty: 2years

SB



*Part number example:

If choose C type for CAT5UTP cable, the part number is C5UTP

Related Products



RJ45 Tool Bag



Inline Coupler



Junction Box



Face Plate



Patch Panel